

SteriLUX®

0.2 µm VTH-grade Standard Capsule Filter (CS/CL Model)

Description

SteriLUX® is hydrophilic PVDF membrane filter with high flow rates, high throughputs, low protein binding properties and broad chemical compatibility. It is recommended for sterilizing filtration and bioburden reduction of pharmaceutical preparations, active ingredients, biopharmaceuticals, parenterals, vaccines, biologicals including dilute protein solutions, cell and tissue culture media, media additives, ophthalmic and other dilute preservative solutions, UPW, chemicals, alcohols and sanitizing agents.

The SteriLUX® VTH0.2 filter capsule is 100% integrity tested during manufacture and has the added benefit of quality certification that meets the critical demands of the pharmaceutical, biotechnology and related industries.

Materials of Construction

All components of the SteriLUX® filter capsule are either animal component free or in compliance with EMEA/410/01 Rev. 3 (EDQM 5.2.8 07/2011:50208), and US Code of Federal Regulations 9 CFR 94.18 and 21 CFR 189.5. These materials are listed for food contact use in the Code of Federal Regulations (CFR), Title 21, as below:

Membrane:	Polyvinylidene fluoride	CFR Title 21, 177.2510
Upstream support:	Polypropylene	CFR Title 21, 177.1520
Downstream support:	Polypropylene	CFR Title 21, 177.1520
Outer guard:	Polypropylene	CFR Title 21, 177.1520
Core:	Polypropylene	CFR Title 21, 177.1520
End caps:	Polypropylene	CFR Title 21, 177.1520
Capsule housing:	Polypropylene	CFR Title 21, 177.1520
Sealing method:	Thermal bonding	

Pore Size 0.2 µm

Minimum Bubble Point 50 psi (3.44 bar), water
18 psi (1.24 bar), 60% IPA/40% water
17 psi (1.17 bar), 70 % IPA/30% water

Maximum Diffusion Rate CS: 2.7 mL/min @ 40 psi (2.76 bar), water
CL: 5.7 mL/min @ 40 psi (2.76 bar), water

Bacterial Retention >10⁷ per cm² removal of *Brevundimonas diminuta* per ASTM F838

Operating Characteristics

Operating temperature range: 32 °F to 100 °F (0 °C to 38 °C)
Maximum temperature rating: 160 °F @ 35 psig (72 °C @ 2.4 bar)
Maximum operating pressure: 75 psig @ 100 °F (5.2 bar @ 38 °C), liquid service
Maximum operating pressure: 50 psig @ 100 °F (3.4 bar @ 38 °C), gas service
Reverse operating pressure: 15 psig @ 100 °F (1.0 bar @ 38 °C)

Sterilization

Autoclave: 121 °C to 135 °C (15 to 30 psi, 1 to 2 bar), 30 to 60 minutes, ≥ 3 cycles.
Gamma irradiation: 25 to 40 kGy once. Do not autoclave irradiated capsules.
Capsules must not be in-line steam sterilized.

Biological Safety

SteriLUX® filters meet the requirements as specified in the current USP <88> Class VI plastics, physicochemical, oxidizable substances, and USP <87> cytotoxicity tests. Bacterial endotoxin levels in aqueous extracts of SteriLUX® filters are less than 0.5 EU/mL, as determined using the *Limulus* amoebocyte lysate (LAL) test <USP> 85. No binders, adhesives or surfactants are used in the construction of SteriLUX® filters. Filters comply with European Commission Regulation No 10/2011.

Quality Assurance

Each SteriLUX® VTH0.2 is supplied with a Certificate of Quality verifying the high standards and superior performance of the product. SteriLUX® filters comply with the Food and Drug Administration Code of Federal Regulations, Title 21, Parts 210 and 211. Product is manufactured and packaged in a cleanroom facility that, through voluntary compliance, meets or exceeds FDA Good Manufacturing Practice Standards. To ensure product reliability, Meissner’s Quality Assurance staff continually audits the manufacturing process for conformance to its Quality Management System. Each SteriLUX® filter is integrity tested during manufacture and is clearly marked with filter type, lot number and serial number.

Ordering Guide

C S 2 VTH 0.2 - 00 2

Capsule Options	
Standard capsule	C
Sterile capsule	G
Opaque shell	O

Vent/Drain Ports	
0	No vent/drain port
1	One luer port with cap, outlet side
2	Standard; two luer ports with caps
4	Two sanitary valves with hose barbs
5	One sanitary valve with hose barb, outlet side
6	One sanitary valve with hose barb, inlet side

Effective Filtration Area	
3.3 ft ² (0.31 m ²)	L
1.6ft ² (0.15 m ²)	S

Inlet/Outlet Connections			
00	1" sanitary (TC) flange	44	1/4" MNPT
02	1" sanitary flange in; 3/8" hose barb out	55	3/8" FNPT
0C	1" sanitary flange in; 1/2" hose barb out	66	3/8" MNPT
CC	1/2" hose barb (rigid tubing)	77*	3/4" sanitary flange
22	3/8" hose barb	88	3/4" hose barb
2B	3/8" hose barb w/ filling bell	99	1/2" hose barb (flexible tubing)

Housing Material Designator	
Standard polypropylene	(blank)
Gamma-stable polypropylene, animal component free (ACF)	2

Product	Grade	Retention Rating
SteriLUX® hydrophilic PVDF membrane	VTH	0.2 µm

*3/4 sanitary flange fitting option is only available for CS2 and CL2 Capsules.

Additional information about this filter product is available in the SteriLUX® Green Docs document at www.meissner.com/green-docs.

SteriLUX® is a registered trademark of Meissner Filtration Products.
© 2017 Meissner Filtration Products, Inc. All rights reserved.